Cat 7A+ 22AWG S/FTP LSZH IEC 60332-3 55% Braid Horizontal Cable

Copper | Cables | Cat 7A





RiT Category 7A S/FTP Cable, 22 AWG solid wires, 4 individually AL-Foil shielded twisted pairs, Overall braiding 55%, with drain wire, cabled together and jacketed with LSZH compound.

KEY APPLICATIONS

- Indoor use
- 10/100/1000Base-T, 10G
- Power over Ethernet

KEY FEATURES

- Designed to support Cat 7A Link and Channel performance
- Electrical performance up to 1500 MHz
- Supports PoE Type 4 applications (IEEE 802.3bt)
- Exceeds the requirements of ISO/IEC 11801
- 100% factory tested

STANDARDS COMPLIANCE

- IEC 61156-5/7
- ISO/IEC 11801-1
- IEEE 802.3bt (4PPoE)
- IEC 60332-1
- IEC 60332-3
- RoHS 2 Directives 2011/65/EU, 2015/863/EU

RiT Tech (Intelligence Solutions) Ltd.
20 Atir Yeda St. Kfar Saba, 4464315, Israel | Tel: +972-77-2707270 | Fax: +972-3-6474115 | www.rittech.com

Cat 7A+ 22AWG S/FTP LSZH IEC 60332-3 55% Braid Horizontal Cable

Copper | Cables | Cat 7A

TECHNICAL SPECIFICATION

Cable Construction	
Outer Jacket Diameter	Ø8.5 mm
Outer Jacket Material	FR-LSZH
Conductor Material	Annealed Bare Copper
Conductor Size	22 AWG
Conductor Construction	Solid
Insulation Material	SFS PO
Conductor unit lay-up	Twisted Pairs
Number of conductors	8
Drain-wire (when applicable)	Ø0.4 mm Tinned Copper
Color Code	White - Blue, White - Orange, White - Green, White - Brown
Ind. Pair Shield Design	Helically applied Aluminum foil 100% coverage
Ind. Pair Shield Material	Aluminum/Polyester Foil
Overall Shielding	Tined Copper wire braid 55% coverage

Electrical Characteristics	
Frequency Range	1- 1500 MHz
Impedance	100 Ω
Transfer Impedance	Grade 1
Coupling Attenuation:	Type I
Max. DC Resistance	57 Ω/km@20°C
Max. Resistance Unbalance	2 %
Capacitance	44 pF/m
Capacitance Unbalance	1.2 pF/m max.
Velocity of Propagation	80 % nom.
Propagation Delay Skew	20 ns/100m max.
Dielectric Strength:	700 V/minute
Dielectric Strength to Shield	700 V/minute
Min. Insulation Resistance	5 GΩ•km

Mechanical Properties	
Minimum Bending Radius	60 mm
Tensile Strength - Short Term	180 N
Operating Temperature	-30°C to +70°C
Installation Temperature	0°C to +50°C
Wight	80 kg/km

ORDERING INFORMATION

P/N	DESCRIPTION
R2712010	CAT 7A+, S/FTP, Horizontal Cable, 22AWG, 55% Braid, LSZH, IEC 60332-3, with Drain Wire, Black, 500 m Reel
R2712020	CAT 7A+, S/FTP, Horizontal Cable, 22AWG, 55% Braid, LSZH, IEC 60332-3, with Drain Wire, White, 500 m Reel

4559780_A0

RiT Tech (Intelligence Solutions) Ltd.
20 Atir Yeda St. Kfar Saba, 4464315, Israel | Tel: +972-77-2707270 | Fax: +972-3-6474115 | www.rittech.com