50 Port ISDN/Telephone Patch Panel

Features

- Simple labor-saving assembly and installation
- Unique assembly fixture
- Compatible with 22-26 AWG
- High durability and reliability

50 Port ISDN/Telephone Patch Panel

Specifications

Standards Compliance

- ANSI/TIA-568.2-D Cat. 3
- ISO/IEC 11801-1, Class C
- ANSI/EIA-310-D 19” Racks
- IEC 60603-7 for keystone snap-on aperture
- RoHS/Reach Compliant

Interface

- **Front Interconnection (patch cords side)**
  50 eight position unshielded RJ-45 modular jacks.
- **Back Interconnection (cabling side)**
  25 eight-position IDC blocks, accept 22 to 26 AWG wires. Each fourth position of the eight position block, is connected to upper / lower front jacks, using 110 or Krone‘s termination tool. Use Installation instructions and IDC coding for the proper termination

Note: Termination tools must be ordered separately.

50 Port ISDN/Telephone Patch Panel

Specifications

Electrical Specifications

General

- **Physical**

  Height: 44.1mm / 1.74" (1U)

  Width: 482.6mm / 19"

  Depth: 105.0mm / 4.13"

  Weight: ~1.0 kg (2.2 lb.)

- **Material**

  Steel

- **Colors**

  Black background with white silk-screened markings

- **Environment**

  Temperature:

  Storage: -40 to 70C

  Operational: -10 to 60C

  Humidity: 0-93% non-condensing

50 Port ISDN/Telephone Patch Panel

Ordering Information

Number	Description
R3260031	Cat 3 ISDN Patch Panel, UTP, 50 Ports, 1U